



PORTUGUÊS	ESPAÑOL	ENGLISH	DEUTSCH
<input checked="" type="checkbox"/> POSIÇÃO HORIZONTAL E VERTICAL (IPLP12864)	PRESENTATION HORIZONTAL OU VERTICAL	HORIZONTALLY OR VERTICALLY MOUNTED	HORIZONTAL UND VERTIKAL POSITION
<input checked="" type="checkbox"/> SUPORTA 2 LOGOTIPOS	2 LOGOS PERSONALIZACION	UP TO 2 COMPANY LOGOS	BIS 2 FIRMENLOGOS
<input checked="" type="checkbox"/> DATA	PRESENTACIÓN DE FECHA	DATE	DATUM
<input checked="" type="checkbox"/> HORA	PRESENTACIÓN DE HORA	TIME	UHRZEIT
<input checked="" type="checkbox"/> TEMPERATURA	PRESENTACIÓN DE TEMPERATURA	TEMPERATURE	TEMPERATUR
<input checked="" type="checkbox"/> SINAL DE PROIBIDO FUMAR	PRESENTACIÓN DE PROHIBIDO FUMAR	SYMBOL NO SMOKE	RAUCHEN VERBOTEN
<input checked="" type="checkbox"/> ATÉ 31 PISOS	ATE 31 PISOS	UP TO 31 FLOORS	BIS 31 ETAGEN
<input checked="" type="checkbox"/> SETAS DE MOVIMENTO	FLECHAS DE DIRECCIÓN	UP AND DOWN ARROWS	FAHRTRICHTUNGEN
<input checked="" type="checkbox"/> FORA DE SERVIÇO	FUERA DE SERVICIO	SYMBOL OUT OF SERVICE	AUSSER BETRIEB
<input checked="" type="checkbox"/> BOMBEIROS	BOMBEROS	FIREMAN	FEUERWEHR
<input checked="" type="checkbox"/> EXCESSO DE CARGA COM AVISO ACUSTICO	SOBRECARGA CON AVISO ACUSTICO	OVERLOAD WITH ACOUSTIC WARNING	TRAGKRAFT UEBERSCHRITTEN
<input checked="" type="checkbox"/> CHAMADA DE EMERGÊNCIA	LLAMADA DE EMERGENCIA	EMERGENCY CALL	NOTRUF
DIMENSÕES: IPLP12864 : 128 X 64 PIXELS 70 MM X 38 MM 65 MM X 33 MM IPLP240128 : 240 X 128 PIXELS 128 MM X 74 MM 108 MM X 58 MM	MEDIDAS: IPLP12864 : 128 X 64 PIXELS 70 MM X 38 MM 65 MM X 33 MM DG240128 : 240 X 128 PIXELS 128 MM X 74 MM 108 MM X 58 MM	DIMENSIONS : IPLP12864 : 128 X 64 PIXELS 70 MM X 38 MM 65 MM X 33 MM DG240128 : 240 X 128 PIXELS 128 MM X 74 MM 108 MM X 58 MM	ABMESSUNGEN : IPLP12864 : 128 X 64 PIXELS 70 MM X 38 MM 65 MM X 33 MM DG240128 : 240 X 128 PIXELS 128 MM X 74 MM 108 MM X 58 MM
<input checked="" type="checkbox"/> LOGICA POSITIVA E NEGATIVA	PRESENTACIÓN MODO NORMAL O MODO NEGATIVIZADO	POSITIVE AND NEGATIVE LOGIC	POSITIVE ODER NEGATIVE DARSTELLUNG
<input checked="" type="checkbox"/> CÓDIGO BINÁRIO BCD E CÓDIGO GRAY	CÓDIGO BINARIO BCD OU CÓDIGO GRAY	BCD BINARY CODE OR GRAY CODE	FUNKTIONIERT MIT BINARY BCD ODER GRAY CODE
<input checked="" type="checkbox"/> COMUNICAÇÃO RS-485	COMUNICACIÓN RS-485	RS-485 COMMUNICATION	RS-485 KOMMUNIKATION
<input checked="" type="checkbox"/> Cor Azul	COLORE : AZUL	COLOR: BLUE	FARBE : BLAU
<input checked="" type="checkbox"/> Tensão: 21 ~ 36V DC	ALIMENTACION : 21~36V	VOLTAGE:21 ~ 36V DC	BETRIEBSSPANNUNG : 21~36V DC

